

Product Record

This documentation should be issued with and kept for each item or system.
Please see the product label for the details required below.
Consult this guide for advice on inspection, maintenance, lifespan, etc.

**UK
CA
0120**
CE0598

**User Guide:
Slings &
Lanyards**

**User Guide:
Slings &
Lanyards**

User's Name:			
Date of Manufacture:		Date of Purchase:	
Date of First Use:		Product Serial No.:	
Inspection Record			
Date	Reason for Entry e.g. periodic examination or repair	Name of Inspector	Date of next Inspection

Declaration of Conformity

The EU Declaration of conformity is available by scanning the QR code or visiting www.sar-products.com/eu-doc/



Certificate of Conformity

We certify that SAR Slings & Lanyards conform to EN354:2010, EN566:2017, EN795:2012 Type B & PD CEN/TS 16415:2013 Type B.
Other components used with this product must conform to the relevant EN standard's or those of the country use.

Signature  For SAR Products Ltd.

Conforms to:

EN354:2010
EN566:2017
EN795:2012 Type B
(one person load)
PD CEN/TS 16415:2013 Type B
(two person load)

Conforms to:

EN354:2010
EN566:2017
EN795:2012 Type B
(one person load)
PD CEN/TS 16415:2013 Type B
(two person load)



Specialist Access & Rescue
Products Ltd.

Sarena House,
Vulcan Street
Oldham, OL1 4LQ



Specialist Access & Rescue
Products Ltd.

+44 (0)161 621 0309
sales@sar-products.com
www.sar-products.com

Slings & Lanyards - Conform to EN354:2010, EN566:2017, EN795:2012 **Type B** when used for a one person load & PD CEN/TS 16415:2013 **Type B** when used in rescue for a two person load. When used for rescue using a 2 person load then the equipment is not classed as PPE under regulation (EU) 2016/425.

Important

Please read, study and understand these instructions before use. THE MATERIALS USED IN THIS PRODUCT ARE HIGH SPEC POLYESTERS.

Use

The SAR Slings and Lanyards have been designed for your protection and therefore are (PPE) personal protective equipment and not lifting equipment. It is a safety anchor for rescue and technical access (in normal climatic conditions). It is suitable for many other applications but please check with the manufacturer first. Use only as instructed and with compatible items of equipment. These should conform to the relevant European standards or those your country follows.

Check that the safe function of any one component within a system will not interfere with the safe function of another. Twists in slings or lanyards can cause problems and weakness in other components. Neatness is strength. Users should be trained, competent or under the supervision of such a person. A suitable rescue plan should be in place before the use of the equipment.

The slings or lanyards must not be used for energy absorption without the use of an energy absorber conforming to EN355 and shall not exceed 2m in length (including terminations connectors and the shock pack).

If a risk assessment is carried out before the start of the work shows that loading in the case of use over a sharp edge is possible, appropriate precautions should be taken. The user should always minimise the slack in the anchor stop near a fall hazard.

The system should be arranged so that the direction of any stress applied to a connector shall lie down its major axis. All gates must be locked. Wet or icy conditions may have an effect on the sling or lanyard.

Note: The information in this guide meets the PPE EU Regulations 2016/425. It is not comprehensive and cannot be substituted for the correct training, which can be provided if required. If in any doubt please don't hesitate to contact us.

Safety

The safety provided by this sling or lanyard depends on its strength, the anchor/belay and the skill of the user. The strength will be reduced through age, wear and tear, abrasion, high impact loads, tight/sharp edges, some chemical (e.g. alkalis, etc.), UV or failure to store and maintain as recommended.

This list is not exhaustive. As a rule, but not always (so be careful) if the sling or lanyard has a high strength rating then there is less chance of failure due to the points outlined above; however, there are exceptions which include chemical attack or very high or low temperatures.

Do not alter the product in any way. Any sling or lanyard subjected to a minor fall should be examined and discarded if there is any sign of defect or any doubts about its safety.

Lifespan

This is difficult to estimate but we advise as follows:

Do not use more than ten years after the date of manufacture. If the product is stored correctly, the working life can vary between a single use in extreme circumstances (e.g. highly chemical environment, serious fall), and ten years depending on how the product is used. The working life will be reduced through age, general wear and tear, abrasion, cuts, damage to component parts, inappropriate ancillary equipment, high impact load, prolonged exposure to UV light including sunlight, elevated temperature (50° C max) exposure to some chemicals (e.g. alkalis, etc.) or failure to store and maintain as recommended. This list is not exhaustive.

Inspection

Before each use visually inspect to ensure the product is in serviceable condition and operates correctly. An examination should be carried out at least every 6 months by a competent person authorised by the manufacturer. These inspections should be recorded paying particular attention to areas of potentially high wear such as attachment points, buckles, connectors and sewn joints. Inspect as follows:

- Textiles: Check for cuts, tears, abrasions, damage due to deterioration, contact with heat, alkalis or other corrosives.
- Sewing: Check for broken, cut or worn threads.
- Metals: Check for cracks, distortion, corrosion, wear by abrasion, burrs, worn or loose rivets or screws, discolouration caused by extreme heat (greater than 100° C), broken springs, frays or cuts, seizure of moving parts, broken or missing components.

Immediately withdraw from service any items showing defects. The user's life depends on it. All repair work should be carried out by the manufacturer or with their authorisation.

Anchorage

Anchor points should always be strong enough to hold the user particularly in the event of a fall. They should be at least 15kN. A webbing lanyard or rope should be effectively sleeved to protect against damage if structural members with sharp edges cannot be avoided as anchorage points.

Meanings of Markings

- The name, trademark or any other means of identification provided by the manufacturer or supplier.
- The batch or serial number.
- The year of manufacture.
- CE... EC logo followed by the number of the notified body.
- EN... European standard attributed to this PPE.
- Product description and/or reference.

- BL... Breaking load in kN.
 - Working length or overall circumference.
- Strengths quoted are when the product is tested new and are in accordance with the manufacturer's test methods or to the appropriate standard. Any weights and measurements are approximate. Nothing in this document affects the consumer's statutory rights.

Notified body

SGS FIMKO OY, Takomotie 8, FI-00380 Helsinki, Finland. Notified Body No: 0598

Approved Body UKCA

SGS United Kingdom Limited - Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN
Approved Body No: 0120

Maintenance

Always keep the product clean and dry. Any excess moisture should be removed with a clean cloth and then allowed to dry naturally in a warm room away from direct heat.

Cleaning

Rinse in clean cold water. If still soiled, wash in clean warm water (max.40°C) with pure soap or a mild detergent (within pH range of 5.5 to 8.5) You can use a washing machine but first place the product in a suitable bag to protect against mechanical damage. Rinse properly in clean cold water.

Chemicals

Avoid contact with any chemicals which could affect the performance of the product. If contact occurs or is suspected then discard the product immediately. If used in a marine environment thoroughly rinse in clean cold water and dry after each use.

Storage


After cleaning, store unpacked in a cool, dry, dark place away from excessive heat sources or other possible causes of damage. Do not store wet. If a long shelf life is required it is advisable to store in a moisture proof package (e.g. polythene bag).

Warning

Working at height is hazardous. It is the user's responsibility to ensure understanding of the correct and safe use of this equipment, to use it only for the purposes for which it is designed and to practise all proper safety procedures

Please note, the information provided in this user guide is not exhaustive, it is not a substitute for a comprehensive instruction and training by a competent person.

SAR Products is not responsible for any consequences, direct, indirect or accidental, resulting from the use of its products. If you are unsure about the correct use of this product, please contact us.



Cambium Saver

Approved secure anchor point

